



- Class AB power amplifier full MOSFET
- Unregulated power supply
- High level input with autosense power-on
- Cross Over with switchable High Pass or Low Pass filter
- Slot for G_cards
- Remote Volume Control RTC (optional)

POWER SUPPLY

Power supply voltage	11 - 16V
DC-DC converter typology	Unregulated – Push Pull
Internal fuse	2 x 40A
Autosense power-on	in High level mode only
Overall efficiency	>60%

OUTPUT POWER RMS

Stereo power RMS @ 4Ω	130W x 4
Stereo power RMS @ 2Ω	175W x 4
Bridge power RMS @ 4Ω	350W x 2

SIGNAL INPUT

Input sensitivity range	0.35 ÷ 16V
Input impedance (High level mode)	470Ω (floating)
Input impedance (Low level mode)	10kΩ (ground referenced)
Input CMRR	> 80dB
Input interface configuration	fully differential

FEATURES

Onboard crossover filter configuration	OFF - LP - HP
HP and LP filter range	20 ÷ 225Hz
HP and LP filter slope	12dB/oct
G-CARD compatibility	All listed in the catalogue

CONNECTIONS

Low level input	RCA
High level input	RCA
Remote control RTC (optional)	Modular jack

APPEARANCE

Dimensions	310x200x50mm
Weight	2.7Kg
Color	Black
Finishing	Powder coating

COMPATIBLE ACCESSORIES:

G-CARDS
RTC

